

Pyroplex


Intumescent Acrylic Sealant



310ml Sealant Tube 2WT310PY



600ml Foil Pack 2SWT600



10 Litre Tub 2WT10LPY



Pyroplex® Intumescent Acrylic Sealant is a one-part high modulus, halogen free material. The product is designed for use in internal application. It is suitable for perimeter pointing around services and for use in low movement linear joints in walls and floors. Pyroplex Intumescent Acrylic Sealant can provide up to 240 minutes fire resistance integrity depending on application and backing material required. The material is compatible with common building materials.

Performance and Certification: Fire – BS 476: Part 20/22 | Fire – BS EN 1366-4 | IFC Certificate No. IFCC1366

Test Standard

- BS 476: Part 20/22 | BS EN 1366-4 | IFC Certificate No. IFCC1366

Features

- Fire resistance up to 4 hours (240 minutes)
- Excellent adhesion with common building materials
- Movement capability $\leq 7.5\%$
- Cartridges and foil packs are fully recyclable
- Internal use only

Material

- A water-borne acrylic sealant with fire and smoke resisting capability for internal gap sealing

Supplied

- 310 ml cartridges, 600 ml foil pack or 10 Litre tubs

Glazing Beads

- Available in white. Other colours are available on request

Application

Pyroplex® Intumescent Acrylic Sealant has been designed for:

- Sealing linear gap joint seals up to 40mm width
- Sealing around plastic pipe or cable penetrations which have been protected with the recommended Pyroplex intumescent product eg. CE Marked Pipe Collar, CE Marked Pipe Wrap

Health and safety

- Store between 5°C and 30°C in unopened condition
Do not expose to frost
- Use in well ventilated areas
- Tools can be cleaned with soap and water