


# TOP PLUS

CE1328TPP



## ITEM SIZE (mm)

13 x 28

## GROOVE SIZE (mm)

13,1 x 28

## AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130

## MATERIALS

**EXTERNAL PROFILE** 6060 T6 aluminium alloy

**INTERNAL PROFILE** 6060 T6 aluminium alloy

**AVAILABLE FINISHING** Mill

**MECHANISMS** Nylon PA6 30% Fiberglass reinforced

**SEAL** T + A. Co-extruded seal in self-extinguishing thermoplastic. Color: grey

**CLOSING END-CAP** Included. Nylon PA6 30% Fiberglass reinforced. Color: black

**ACTIVATION PLUNGER** 1. Self directing articulated metal plunger with nylon cap, adjustable with 3mm Allen wrench. Nylon PA6 30% Fiberglass reinforced. Color: black.

## TECHNICAL CHARACTERISTICS

**MAXIMUM DROP (mm)** 18

**WORKING TEMPERATURES (C°)** -35° / + 200°

**FIXING TYPE** 2F. With premounted screws (3,5x20 countersunk nickel plated screws) or

1F. With stainless steel brackets (includes 3,5x20 countersunk nickel plated screws).

## CERTIFICATES

**WORKING CYCLES** 200.000 (internal test)

**ACOUSTIC INSULATION** **44dB Rw** - Cert. n. PB Z10-G03-04-en-01 - IFT Rosenheim

**FIRE RESISTANCE** /

**SMOKE TESTED** /



# TOP PLUS

CE1328TPP

ITEM LENGHT mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,139	7,70	50	330 -> 280
430	0,181	9,80	135	430 -> 295
530	0,223	11,90	200	530 -> 330
630	0,265	14,00	200	630 -> 430
730	0,307	16,10	200	730 -> 530
830	0,349	18,20	200	830 -> 630
930	0,391	20,30	200	930 -> 730
1030	0,433	22,40	200	1030 -> 830
1130	0,475	24,50	200	1130 -> 930
/	/	/	/	/
/	/	/	/	/
/	/	/	/	/
/	/	/	/	/
/	/	/	/	/
/	/	/	/	/
/	/	/	/	/
/	/	/	/	/

## PACKAGING

**MINIMUM PACKAGING** 5 pieces

**BOX PACKAGING** 50 pieces (except where noted)

### ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.

