

Fire Door Foam™

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** FAS Fire Door Foam™
- 1.2 Product code:** FAS-FDF-750G
- 1.3 Relevant identified uses of the substance or mixture and uses advised against:** Assembly foam
Application of the substance / the mixture Construction chemicals
Uses advised against Uses other than those recommended.
- 1.4 Details of the supplier of the safety data sheet:**
 Fire & Acoustic Seals Limited
 Units 6-11 Spartan Industrial Estate,
 Brickhouse Lane,
 West Bromwich, B70 0DH,
 United Kingdom
 Phone: +44 (0)121 521 2179
 Email: sales@fireandacousticseals.co.uk
 www.fireandacousticseals.co.uk
- 1.5 Emergency telephone number:**
 +44 (0)121 521 2179 (Office Hours 08:00 to 17:00)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS02 flame

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 Carc. 2 H351 Suspected of causing cancer.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.



GHS07



GHS02



GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

diphenylmethanediisocyanate, isomers and homologues
tris(2-chloro-1-methylethyl)phosphate

- **Hazard statements**

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

- **Precautionary statements**

P102 Keep out of reach of children.
P260 Do not breathe gas.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

As from 24 August 2023 adequate training is required before industrial or professional use. Further information at: www.feica.eu/PUinfo

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Do not spray on an open flame or other ignition source.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

EUH204 Contains isocyanates. May produce an allergic reaction.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Determination of endocrine-disrupting properties**







The product does not contain substances with endocrine disrupting properties.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 **Substance:** Non-applicable

3.2 Mixtures

Chemical description: Mixture of substances listed below with nonhazardous additions.

CAS: 9016-87-9 EC: 618-498-9	diphenylmethanediisocyanate, isomers and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %		30 - 60 %
CAS: 1244733-77-4 EC: 807-935-0 Reg.nr.: 01-2119486772-26-XXXX	diphenylmethanediisocyanate, isomers and homologues Carc. 2, H351; Acute Tox. 4, H302; Aquatic Chronic 3, H412		<20%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280		<15%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280		<15%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure Flam. Gas 1A, H220; Press. Gas (Comp.), H280		<15%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1A, H220; Press. Gas (Comp.), H280		<10%

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- **After skin contact:**

Remove uncured foam using a piece of cloth and an unaggressive solvent, e.g. ethanol. Wash your hands and the cleaned skin surface using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

- **Suitable extinguishing agents:**

Carbon dioxide.

Fire-extinguishing powder.

Foam.

Water spray.

Use fire extinguishing methods suitable to surrounding conditions.

- **For safety reasons, unsuitable extinguishing agents:** Water with full jet.

5.2 Special hazards arising from the substance or mixture:

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters:

- **Protective equipment:**

Wear a self-contained respiratory protective device.

Wear a fully protective suit.

- **Additional information:** Cool endangered receptacles with water spray.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from ignition sources.

Wear protective clothing.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform the respective authorities in case of seepage into the water course or sewage system.

Do not allow to enter sewers/surface, or groundwater.

6.3 Methods and material for containment and cleaning up:

Uncured foam adheres easily, hence it should be removed with caution. Remove instantly using a piece of cloth and solvents, e.g. acetone, alcohol. Remove cured foam mechanically.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections:

See Section 13 for disposal information.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Open and handle the receptacle with care.

Do not pierce or burn even after use. Use only as directed on the label.

Do not mix with any other chemical products.

- **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities:

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

This product is subject to regulations governing the storage of highly flammable aerosol products.

Storage rooms should be equipped with heat and smoke detectors.

Electrical equipment should be explosion-proof.

- **Information about storage in one common storage facility:**

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

Store away from oxidising agents.

Store away from foodstuffs.

Store away from plastic, rubber, aluminum, light-metals.

- **Further information about storage conditions:**

Store in vertical position in closed original containers.

Store receptacle in a well ventilated area.

Protect from frost.

Store at temperature from +5°C to +30°C.

SECTION 7: HANDLING AND STORAGE Continued...

Store under lock and key and out of the reach of children.
Keep container tightly sealed.
Protect from heat and direct sunlight.

7.3 Specific end use(s):

Field of application of the product is described in Technical data sheet (TDS).

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Control parameters: Substances whose occupational exposure limits have to be monitored in the work environment

CAS: 115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m³, 1000 ppm

- **Regulatory information** IOELV: (EU) 2019/1831

• DNELs

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

Oral	DNEL	20 mg/kg/Tag (General population, consumers)
Dermal	DNEL	0.05 mg/kg/Tag (General population, consumers)
Inhalative	DNEL	0.05 mg/m ³ (General population, consumers) 0.05 mg/m ³ (Workers)

• PNECs

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

(freshwater)	1 mg/l
(freshwater)	0.1 mg/l
(Soil)	1 mg/kg

- **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls:

- **Individual protection measures, such as personal protective equipment**

- **General protective and hygienic measures:**

Do not inhale gases/fumes/aerosols.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash your hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- **Respiratory protection:**

In case of brief exposure or low pollution, use a respiratory filter device. In case of intensive or longer exposure, use a self-contained respiratory protective device.

- **Hand protection**



Protective Gloves

EN 374

The glove material has to be impermeable and resistant to the product / the substance / the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

Polyethylene gloves.

Recommended thickness of the material: \approx 0.020 mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

Short-term contact \geq 10 min (EN 374)

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection



Tightly sealed goggles

• Body protection:



Protective work clothing.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- **General Information**
- **Physical state** Liquid
- **Colour:** Different according to colouring
- **Odour:** Characteristic
- **Odour threshold:** Not determined
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** Not applicable, as aerosol
- **Flammability** Extremely flammable aerosol.
- **Lower and upper explosion limit**
- **Lower:** +/- 1.5 Vol %
- **Upper:** +/- 11.0 Vol %
- **Flash point:** <0 °C (propellant)
- **Auto-ignition temperature:** Not specified
- **Decomposition temperature:** Not determined
- **pH** -
- **Viscosity:** Not applicable
- **Kinematic viscosity** Not determined
- **Solubility**
- **water:** Insoluble
Reacts with water
- **Partition coefficient n-octanol/water (log value)** Not determined
- **Vapour pressure:** >500 kPa (in the container)
< 1*10⁻⁵ mmHg w 25°C (MDI)
- **Density and/or relative density**
- **Density at 20 °C:** ≤1.3 (PMDI) g/cm³
- **Relative density** Not determined
- **Relative gas density** Not determined.
- **Particle characteristics** Not applicable

9.2 Other information

- **Appearance:** No further relevant information available
- **Form:** Rapidly curing foam dispensed by gaseous propellant from an aerosol container
- **Important information on protection of health and environment, and on safety.**
- **Ignition temperature:** > +350 °C (propellant)
- **Explosive properties:** Heating may cause an explosion.
- **Information with regard to physical hazard classes**
- **Explosives** Not applicable
- **Flammable gases** Not applicable
- **Aerosols** Not applicable

Extremely flammable aerosol.

Pressurised container: May burst if heated.

- **Oxidising gases** Not applicable
- **Gases under pressure** Not applicable
- **Flammable liquids** Not applicable
- **Flammable solids** Not applicable
- **Self-reactive substances and mixtures** Not applicable
- **Pyrophoric liquids** Not applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES Continued...

Pyrophoric solids	Not applicable
Self-heating substances and mixtures	Not applicable
Substances and mixtures, which emit flammable gases in contact with water	Not applicable
Oxidising liquids	Not applicable
Oxidising solids	Not applicable
Organic peroxides	Not applicable
Corrosive to metals	Not applicable
Desensitised explosives	Not applicable

SECTION 10: STABILITY AND REACTIVITY

- 10.1 **Reactivity:** No further relevant information available.
- 10.2 **Chemical stability**
Thermal decomposition/conditions to be avoided:
No decomposition if used and stored according to specifications.
- 10.3 **Possibility of hazardous reactions:** No dangerous reactions known.
- 10.4 **Conditions to avoid:** No further relevant information available.
- 10.5 **Incompatible materials:**
Strongly reacts with water and other substances containing an active hydrogen atom.
- 10.6 **Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

- 11.1 **Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**
Harmful if inhaled.

• LD/LC50 values relevant for classification:		
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues		
Oral	LD50	>10,000 mg/kg (rat) (OECD401)
Dermal	LD50	>9,400 mg/kg (rabbit) (OECD402)
Inhalative	LC50/4h	1.5 mg/l (ATE)
CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate		
Oral	LD50	632-2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4h	>7 mg/l /4-hr (rat)

Primary irritant effect:

- **Skin corrosion/irritation**

Causes skin irritation.

- **Serious eye damage/irritation**

Causes serious eye irritation.

- **Respiratory or skin sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

- **Carcinogenicity**

Suspected of causing cancer.

- **Reproductive toxicity:** Based on available data, the classification criteria are not met.

- **STOT-single exposure**

May cause respiratory irritation.

- **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

- **Aspiration hazard:** Based on available data, the classification criteria are not met.

11.2

- **Information on other hazards**

- **Endocrine-disrupting properties**

None of the ingredients is listed.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity:

· Aquatic toxicity:

· CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

EC50	1,640 mg/l (algae) >1,000 mg/l (daphnia) (OECD202) >100 mg/l (Sedimentation) (OECD209)
LC50	>1,000 mg/l (fish) (OECD)

12.2 · **Persistence and degradability:** Not biodegradable.

12.3 · **Bioaccumulative potential:** Does not accumulate in organisms.

12.4 · **Mobility in soil:** No further relevant information available.

12.5 · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

12.6 · **Endocrine disrupting properties.** For information on endocrine disrupting properties see section 11.

12.7 · Other adverse effects

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

· Recommendation

Must not be disposed of together with household garbage. Do not allow the product to reach the sewage system.

Remove in accordance with applicable legislation.

Dispose of in a safe manner in accordance with local/national regulations.

Do not allow it to enter surface or groundwater.

Assigning a code from the waste catalogue depends on the sector in which the user operates, as well as on arrangements made between the waste generator and a competent environmental protection department.

· European waste catalogue

15 01 11*	metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty
HP3	pressure containers
HP4	Flammable
HP5	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP 13	Sensitising

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

It should be treated in the same way as product residues.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number

ADR, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR, IMDG, IATA AEROSOLS

14.3 Transport hazard class(es)

ADR



Class
Label

2.5F Gases
2.1

IMDG, IATA



	Class Label	2.1 Gases
	Packing group	2.1
14.4	Environmental hazards:	NA
14.5	Marine pollutant:	
	Special precautions for user	No
14.6	Hazard identification number	Warning: Gases
	EMS Number:	
	Maritime transport in bulk	F-D,S-U
14.7	according to IMO instruments	
	Transport/Additional information:	Not applicable
	ADR	
	Remarks:	Exemption from ADR provisions by LQ principal (rule 3.4) <ul style="list-style-type: none"> • Inner packaging, max. 1 litre in capacity; outer packaging – max. gross weight of 30kg. • Inner packaging, max. 1 litre in capacity, based on common ground and covered with shrink film – max. gross weight of 20kg.
	UN “Model Regulation”:	UN 1950 AEROSOLS, 2.1

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

1907/2006/CE Regulation, REACH

1272/2008/CE Regulation, CLP

2020/878/UE Regulation

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a FLAMMABLE AEROSOLS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements:** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements:** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction:** 56, 74
- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**
- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

• **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **REGULATION (EU) 2024/590 on substances that deplete the ozone layer**

None of the ingredients is listed.

- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

- 15.2
- **Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**

SECTION 16: OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long-lasting effects.
EUH204 Contains isocyanates. May produce an allergic reaction.

- **Recommended restriction of use**

The information stated above is based on current knowledge and applies to the product in the form in which it is used. Data concerning this product is presented in order to fulfil safety requirements and not to guarantee its specific properties.

In cases when application conditions are not subject to the manufacturer's control, the responsibility for safe product use and obeying law regulations, in particular, lies on the user's side.

Information is in the appropriate technical data sheet of the product.

- **Version number of previous version: 4**

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage

of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* **Data compared to the previous version altered.**

Points marked with * have changed from the previous version of the card

As from 24th August 2023, adequate training is required before industrial or professional use of this product.

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

10 of 10



**Fire &
Acoustic
Seals**

Fire & Acoustic Seals Ltd Unit 17, Spartan Industrial Estate, Brickhouse Lane,
West Bromwich B70 0DH 0121 521 2179 sales@fireandacousticseals.co.uk
www.fireandacousticseals.co.uk

FAS-FDF/MSDSv5 | Feb 2026